

RGS5.0

MACROM

13 cm 2 WAY SYSTEM

SPECIFICATIONS

MAX POWER:	100 W
RMS Power:	50 W
Frequency response:	50 Hz-25 kHz
Sensitivity:	91 dB
Impedance:	4Ω
Dimensions (DIN):	13 cm (5")
Installation depth:	56 mm
Grilles not included	



- **100W MAXIMUM POWER**
50w RMS for use with a powerful head unit or a 20 to 50W amp
- **ORIENTABLE TWEETER WITH MULTI MOUNTING POSSIBILITIES**
For an optimized staging and every kind of installation
- **POLYPROPYLENE CONE**
For a stronger frequency response and great powerful sound
- **13MM NEODYMIUM BALANCED POLYMER DOME TWEETER**
Smoother frequency response and high power handling
- **FERROFLUID COOLED TWEETER**
for better heat dissipation and more power handling
- **6DB/OCT EXTERNAL PASSIVE X-OVER**
6dB high pass for good coupling between woofer/tweeter
- **Ø25MM ALUMINUM VOICE COIL**
for better heat dissipation and more power handling
- **STRONTIUM MAGNET ON THE WOOFER**
for better efficiency and more power handling
- **EXTENDED VENTED POLE PIECE**
for better heat dissipation which increases the applicable power
- **RUBBER SUSPENSION**
for better reliability and better efficiency
- **NEW PLASTIC GASKET**
To improve the look
- **OUTSTANDING QUALITY PRICE RATIO**
Never seen before ! This sound quality at that price level, incredible !