

# RGS6.0

# MACROM

## 16/16,5 cm 2 WAY SYSTEM

### SPECIFICATIONS

MAX POWER:	120 W
RMS Power:	60 W
Frequency response:	45 Hz - 25 kHz
Sensitivity:	92 dB
Impedance:	4Ω
Dimensions (DIN):	16/16.5 cm
Installation depth:	56 mm
Grilles not included	



- **120W MAXIMUM POWER**  
60w RMS for use with a powerful head unit or a 20 to 60W amp
- **ORIENTABLE TWEETER WITH MULTI MOUNTING POSSIBILITIES**  
For an optimized staging and every kind of installation
- **POLYPROPYLENE CONE**  
For a stronger frequency response and great powerful sound
- **13MM NEODYMIUM BALANCED POLYMER DOME TWEETER**  
Smoother frequency response and high power handling
- **FERROFLUID COOLED TWEETER**  
for better heat dissipation and more power handling
- **6DB/OCT EXTERNAL PASSIVE X-OVER**  
6dB high pass for good coupling between woofer/tweeter
- **Ø25MM ALUMINUM VOICE COIL**  
for better heat dissipation and more power handling
- **STRONTIUM MAGNET ON THE WOOFER**  
for better efficiency and more power handling
- **EXTENDED VENTED POLE PIECE**  
for better heat dissipation which increases the applicable power
- **RUBBER SUSPENSION**  
for better reliability and better efficiency
- **NEW PLASTIC GASKET**  
To improve the look
- **OUTSTANDING QUALITY PRICE RATIO**  
Never seen before ! This sound quality at that price level, incredible !