

UNSA4.1

MACROM

10 cm 2 WAY SYSTEM



SPECIFICATIONS

MAX POWER:	80 W
RMS Power:	40 W
Frequency response:	60 Hz-25 kHz
Sensitivity:	90 dB
Impedance:	4Ω
Dimensions (DIN):	10 cm (4")
Installation depth:	43 mm
Grilles included	

- **80W MAXIMUM POWER**

Cool.....

- **POLYPROPYLENE "TITANIUM" CONE WITH CHROME ACOUSTIC LENS IN THE CENTER**

For good low frequency response with a clear mid range

- **12DB/OCT EXTERNAL MINIATURIZED PASSIVE X-OVER WITH PTC PROTECTION**

12dB high pass for ideal coupling between the woofer and tweeter as well as better tweeter protection. The x-over is very small to be easy installed in every car. The PTC is an active protection to save tweeters

- **20MM SILK DOME TWEETER WITH MULTI MOUNTING KIT**

High quality tweeter for smoother frequency response, and very easy to install in any position.

- **FERROFLUID COOLED TWEETER**

For better heat dissipation and more power handling

- **REINFORCED SPIDER**

For an increase in power handling

- **ANTI-RESONANCE BASKET**

To improve sound quality

- **ALUMINUM VOICE COIL**

For better heat dissipation and more power handling

- **GRILLES WITH MACROM LOGO INCLUDED**

For better flexibility and better look

- **EXTENDED VENTED POLE PIECE**

For better heat dissipation which increases the applicable power

- **RUBBER SUSPENSION AND BARIUM MAGNET**

For better reliability and better efficiency